



iVu BCR

Touch Screen Bar Code Reader

- Totally self-contained image based Barcode reading sensor
- Reads multiple code in a single image
- Compares data read with the expected data
- RS232 serial output and 2 discrete outputs
- 68,5 mm touch-screen LCD display (320 x 240 pixels)
- Robust IP67 housing with integrated lighting
- On-board language-selectable, intuitive GUI
- On-board help function
- Adjustable focus lenses
- USB 2.0 compliant host allows easy updating and diagnostics



iVu
now reads
Bar Codes



more sensors, more solutions

Banner Engineering Europe

Park Lane, Culliganlaan 2F
1831 Diegem, Belgium

Tel: +32 2 456 07 80 • Fax: +32 2 456 07 89

Email: mail@bannereurope.com

Web: www.bannereurope.com

www.bannereurope.com



iVu BCR



Reads all commonly used Codes



DataMatrix (ECC 200)
Linear barcodes
Code 128
Code 39
CODABAR
Interleaved 2 of 5
EAN13
EAN8
UPCE
Postnet
IMB
Pharmacode

iVu BCR Models

	None	Red	White	Infrared
4,3 mm Lens	IVUTBPX04	IVUTBPR04	IVUTBPW04	IVUTBPI04
6 mm Lens	IVUTBPX06	IVUTBPR06	IVUTBPW06	IVUTBPI06
8 mm Lens	IVUTBPX08	IVUTBPR08	IVUTBPW08	IVUTBPI08
12 mm Lens	IVUTBPX12	IVUTBPR12	IVUTBPW12	IVUTBPI12
16 mm Lens	IVUTBPX16	IVUTBPR16	IVUTBPW16	IVUTBPI16
25 mm Lens	IVUTBPX25	IVUTBPR25	IVUTBPW25	IVUTBPI25

Lenses are replaceable and are available separately also. NPN models also available.

Cables (QD)

Model Number	Description	Length
MQDC2S-1206	8-pin M12, Straight with Open Shield Female	2 m
MQDC2S-1215		5 m
MQDC2S-1230		9 m
MQDC2S-1250		15 m
MQDEC-8005-USB	USB/8-pin M12, Straight (Male)*	0,15 m
MQDEC-801-USB		0,30 m

*Longer models and angled connectors also available.

Brackets



SMBIVURAL



SMBIVURAR



SMBIVUB



SMBIVUU

SENSORS



VISION



WIRELESS I/O



INDICATORS



SAFETY



Banner offers a full range of sensing solutions

BANNER ENGINEERING EUROPE
WWW.BANNEREUROPE.COM

